

Appin. No. 10/655,695  
Amdt. dated April 12, 2007  
Response to Office Action Mailed October 20, 2006

PATENT

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A method for displaying timing data generated by simulating a circuit design, the method comprising:
  - receiving the timing data from an EDA tool;
  - selecting ~~relevant~~ first and second signals based on input received from a user;
  - generating a first waveform[[s]] for the ~~relevant~~ first signal[[s]] and a second waveform for the second signal using the timing data;
  - displaying a portion of each of the first and second waveforms in an interactive graphical user interface, wherein the portion of each of the first and second waveform displayed in the interface includes time points of interest to the user;
  - displaying pointers to the time points of interest on the first and second waveforms;
  - receiving edits to the time points of interest in response to a user moving the pointers on the interactive graphical user interface; and
  - updating timing parameters based on the edits to the time points of interest.
2. (Currently Amended) The method of claim 1 further comprising:
  - transmitting the updated timing parameters back to the EDA tool;
  - generating updated first and second waveforms for the ~~relevant~~ first and second signals using updated timing data received from the EDA tool, wherein the updated timing data is generated by simulating the circuit design using the updated timing parameters; and
  - displaying the updated first and second waveforms in the interactive graphical user interface.
3. (Currently Amended) The method of claim 1 wherein:

Appln. No. 10/655,695  
Amdt. dated April 12, 2007  
Response to Office Action Mailed October 20, 2006

PATENT

displaying the portion of each of the first and second waveforms in the interactive graphical user interface further comprises displaying a first waveform of a first clock signal received at a first storage element, and a second waveform of a second clock signal received at a second storage element.

4. (Currently Amended) The method of claim 3 wherein:

displaying the portion of each of the first and second waveforms in the interactive graphical user interface further comprises displaying a third waveform of the first clock signal at first clock source, and a fourth waveform of the second clock signal at a second clock source, the first waveform of the first clock signal being delayed with respect to the third waveform by a first clock skew value, and the second waveform of the second clock signal being delayed with respect to the fourth waveform by a second clock skew value.

5. (Currently Amended) The method of claim 3 wherein

displaying the portion of each of the first and second waveforms in the interactive graphical user interface comprises displaying a launch edge of the first clock signal at which the first storage element releases a data signal, and displaying a latch edge of the second clock signal at which the second storage element captures the data signal.

6. (Currently Amended) The method of claim 5 wherein:

the interactive graphical user interface displays portions of the first waveform of the first clock signal and the second waveforms of the second clock signal that each start with a point in time corresponding to a period before both the launch and latch edges and end with a point in time corresponding to a period following both of those edges.

7. (Original) The method of claim 5 wherein:

the launch edge is a first time point of interest identified by a first one of the pointers on the interactive graphical user interface; and  
the latch edge corresponds to a second time point of interest identified by a second one of the pointers on the graphical user interface.

Appln. No. 10/655,695

PATENT

Amdt. dated April 12, 2007

Response to Office Action Mailed October 20, 2006

8. (Original) The method of claim 5 wherein:

updating the timing parameters based on the edits to the time points of interest further comprises updating a multi-cycle value that represents a number of active edges in the second clock signal between the launch edge and the latch edge.

9. (Original) The method of claim 5 wherein:

updating the timing parameters based on the edits to the time points of interest further comprises inverting the launch edge of the first clock signal, either in a design file or as an input to a static timing verification tool.

10. (Original) The method of claim 5 wherein:

updating the timing parameters based on the edits to the time points of interest further comprises inverting the latch edge of the second clock signal.

11. (Currently Amended) ~~A computer program product implemented on a computer system~~ A computer-readable medium encoded with a computer program, the computer program comprising a set of instructions for providing timing data generated by simulating a circuit design using an EDA tool, ~~the computer program product wherein the set of instructions when executed by a computer cause the computer to:~~

~~code for generating~~ generate at least first and second waveforms for signals using the timing data;

~~code for displaying~~ display a portion of each of the at least first and second waveforms in an interactive graphical user interface, wherein the portion of each of the at least first and second waveforms displayed in the interactive graphical user interface includes time points of interest to the user;

~~code for displaying~~ display pointers to the time points of interest on the waveforms;

~~code for generating~~ generate new timing parameters based on edits to the time points of interest received from the user, wherein the user moves the pointers on the interactive graphical user interface to generate the edits;

Appln. No. 10/655,695

PATENT

Amdt. dated April 12, 2007

Response to Office Action Mailed October 20, 2006

~~code for generating~~ generate updated waveforms for the signals using updated timing data, wherein the EDA tool generates the updated timing data by compiling, simulating and performing verification analysis on the circuit design using the new timing parameters; ~~and~~  
~~code for displaying~~ display the updated waveforms in the interactive graphical user interface[[]; and]]

~~a computer-readable medium for reading the codes.~~

12. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 11 wherein:

the ~~code for displaying~~ display of the portion of each of the waveforms in the interactive graphical user interface further comprises ~~code for displaying~~ display of each of the portions of the waveforms in synchronism.

13. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 11 wherein:

the timing data generated by the EDA tool includes periods of a plurality of clock signals, duty cycles of the clock signals, offsets between the clock signals, and clock skews between sources of the clock signals and circuit elements that receive the clock signals.

14. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 11 wherein:

the ~~code for displaying~~ display of the portion of each of the waveforms in the interactive graphical user interface further comprises ~~code for displaying~~ display of a first waveform of a first clock signal received at a first circuit, and ~~code for displaying~~ display of a second waveform of a second clock signal received at a second circuit.

15. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 14 wherein:

the ~~code for displaying~~ display of the portion of each of the waveforms in the interactive graphical user interface further comprises ~~code for displaying~~ display of a third

Appln. No. 10/655,695  
Amdt. dated April 12, 2007  
Response to Office Action Mailed October 20, 2006

PATENT

waveform of the first clock signal at a first clock source, and a fourth waveform of the second clock signal at a second clock source,

wherein the first waveform is delayed with respect to the third waveform by a first clock skew value, and the second waveform is delayed with respect to the fourth waveform by a second clock skew value.

16. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 15 wherein the ~~code for displaying display of~~ the pointers to the time points of interest on the waveforms further comprises:

~~code for displaying display of~~ a first pointer to a launch edge of the first waveform that triggers a first latch to capture a data signal; and

~~code for displaying display of~~ a second pointer to a latch edge of the second waveform that triggers a second latch to capture the data signal.

17. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 16 wherein the ~~code for displaying display of~~ the pointers to the time points of interest on the waveforms further comprises:

~~code for displaying display of~~ a third pointer to an edge of the third waveform that corresponds to the launch edge of the first waveform; and

~~code for displaying display of~~ a fourth pointer to an edge of the fourth waveform that corresponds to the latch edge of the second waveform.

18. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 16 wherein ~~the computer generates:~~

~~the code for generating~~ the new timing parameters based on the edits to the time points of interest ~~further comprises code for~~ by changing a multi-cycle value that represents a number of active edges in the second clock signal from the launch edge to the latch edge in response to the user moving the first or the second pointer on the interactive graphical user interface.

Appln. No. 10/655,695

PATENT

Amdt. dated April 12, 2007

Response to Office Action Mailed October 20, 2006

19. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 17 wherein the computer generates:

~~the code for generating~~ the new timing parameters based on the edits to the time points of interest ~~further comprises code for~~ by changing a multi-cycle value that represents a number of active edges in the second clock signal from the launch edge to the latch edge in response to the user moving the third or the fourth pointer on the interactive graphical user interface.

20. (Currently Amended) The ~~computer program product~~ computer-readable medium according to claim 11 wherein the circuit design is a design for a field programmable gate array.